

Wall Mounting Flood Light

LED Colour Temperature


3000K
6000K

Optics




R8
R0115C050XL 15°
R0124C050XL 24°
R0138C050XL 38°
R0160C050XL 60°

R8



Outer Dimensions

Unit:mm



Remark:

■ Standard pole length of this item is 500mm, 250mm, 100mm.

■ Customized length is available.

Housing Color Option


Basic	Secondary	
Sanded Dark Grey KAP 7037	Silver Grey KAP 9022	Sanded Black RAL9005



Material Specifications

Housing	12# Die-casting dark grey powder coated aluminum. T=60-80μm.Adhesion of ISO class 1/ASTM class 48
Light Window	Tempered glass.T=4mm
LED Driver	Constant Voltage Input,Constant Current Output
LED	NICHIA
Lens	Optical lens,efficiency≥85%
Power Cable	H05RN-F 2X1.0mm² L=2.0m(low voltage) H05RN-F 3X1.0mm² L=2.0m(high voltage)
Operating temperature	-20°C~40°C
Mounting base	Powder coated die-casting aluminum

Adjustable Beam Direction



Item	Light source	Lens	The manufacturer selected lens degree(°)B1/2	Input voltage[V]	Typical operating current(mA)	Typical consumption(W)	Typical luminance(lm)	IK rate
R3XBP0128	1×10W COB	R8	24°	24VDC 120/240	2 4 V = 480 120V = 107 240V = 60	2 4 V = 11.5 120V = 12.6 240V = 12.6	Cool white =1050 Warm white =956	07

