



COB LED Garden Spot Light

LED Colour Temperature


3000K
6000K

Optics



R8
R0115C050XL 15°
R0124C050XL 24°
R0138C050XL 38°
R0160C050XL 60°


R8



15° 24° 38° 60°



Outer Dimensions




Unit:mm

Material Specifications

Housing	12# Die-casting dark grey powder coated aluminum. T=60-80µm,Adhesion of ISO class 1/ASTM class 4B
Light Window	Tempered glass,T=4mm
LED Driver	Constant Voltage Input,Constant Current Output
Reflector	Optical reflector,efficiency≥85%
Power Cable	H05RN-F 2X1.0mm² L=2.0m(low voltage) H05RN-F 3X1.0mm² L=2.0m(high voltage)
Operating temperature	-20°C~40°C
Spike	ABS spike 6b(M4)

Adjustable Beam Direction



Housing Color Option

Basic	Secondary	
Sanded Dark Grey KAP 7037	Silver Grey KAP 9022	Sanded Black RAL9005

Item	Light source	Lens	The manufacturer selected lens degree(°)θ1/2	Input voltage(V)	Typical operating current(mA)	Typical consumption(W)	Typical luminance(lm)	IK rate
R3XB50128	1×10W COB	R8	24°	24V DC 120/240	24V = 480 120V = 107 240V = 60	24V = 11.5 120V = 12.6 240V = 12.6	Cool white =1050 Warm white =956	07

