



Up Beam Type
Mini LED inground light

LED Colour Temperature

2000K
3000K
6000K


Optics

B15
L0110D016LK 10°
L0115D016LK 15°
L0120D016LK 20°
L0130D016LK 30°


Material Specifications

Housing	Aluminum anodized finishing or powder painting
Front ring	Hard chrome plated stainless steel SUS 316 ⁴
PMMA	T=2mm
Cable gland	IP67 Nickel coated copper
Gasket	Silicone seal
Lens	Optical lens, efficiency > 85%
LED Driver	Constant Current Input
Operating temperature	-20°C ~ 40°C
Power Cable	H05RN-F 2X0.5mm ² L=0.3m
Mounting sleeve	ABS 104 ⁴
Dimmable support	Triac PWM 1-10V Dali

B15



Outer Dimensions



B2BNR0157

B2BNS0157

104⁴ Mounting sleeve

Item	Light source	Lens	The manufacturer selected lens degree(°)θ1/2	Input voltage(V)	Typical operating current(mA)	Typical consumption(W)	Typical luminance(lm)	IK rate
○ B2BNR0157	1×2W	B15	20°	3V DC	500	1.5	Cool white =148 Warm white =135	02
□ B2BNS0157	1×2W	B15	20°	3V DC	500	1.5	Cool white =148 Warm white =135	02

