



Up light  
Tiny Type LED Inground Light  
Stainless Steel Front Cover

LED Colour Temperature

2000K  
3000K  
6000K

Optics



**B26**



8°



**B27**



13° 25° 30°

Outer Dimensions

Unit:mm



Material Specifications

|                         |  |
|-------------------------|--|
| Housing                 | 12# Die-casting grey powder coated aluminum, T=60-80µm Adhesion of ISO class 1/ASTM class 4B |
| Front cover             | Hard chromeplated Stainless steel SUS 316L#  |
| Light Window            | Tempered frosted step glass,T=4mm  |
| LED                     | OSRAM  |
| Glass pressure capacity | Full area=254kgs   |
| Operating temperature   | -20°C-40°C   |
| Power Cable             | H05RN-F 2X1.0mm <sup>2</sup> L=0.5m(low voltage)   |
| Mounting sleeve         | ABS 033#   |
| Dimmable Support        | Triac PWM 1-10V Dali   |

| Item         | Light source | The manufacturer selected lens degree(°)θ1/2 | Input voltage(V) | Typical operating current(mA) | Typical consumption(W) | Typical luminance(lm)              | IK rate |
|--------------|--------------|--|------------------|-------------------------------|------------------------|------------------------------------|---------|
| ○ B2YC-R0157 | 1×2.0W OSRAM | 25°  | 24V DC           | 110                           | 2.5                    | Cool white =135<br>Warm white =120 | 03      |

