

Central Ejective Fountain Light
Completely Hard chromeplated Stainless Steel SUS 316# Housing and Accessories



Overheat Sensor Inside



LED Colour Temperature


- 2000K
- 3000K
- 6000K

Optics




- B32
- L0120F024PS 20°
- L0125F024PS 25°
- L0130F024PS 30°
- L0135F024PS 35°
- L0135F024PS 35°

B32



Outer Dimensions

Unit:mm




Material Specifications


Housing	Hard chromeplated molding shaped stainless steel SUS 316#
Light Window	Step tempered glass.T=10mm
Gasket	Silicone gasket
Cable gland	IP68 PG-11 copper with nickel-coated
PCB	Excellent heat conductivity aluminum.coefficient of heat Conductivity2.0w/mk
LED Driver	Constant Voltage Input.Constant Current Output
Power Cable	H07RN-F 2X1.0mm² L=3.0m
Application environment	Temperature of water between -20°C~40°C less than 1 meter depth.
Built-in Overheat Sensor System	Automatic Shutdown at 75°C
Dimmable Support	Triac PWM 1-10V Dali



Warning:
Must be installed under the water to prevent the light from burning up because of over-heating.



Central Ejective



Water jet pipe G11/2"taper

Item	Light source	Lens	The manufacturer selected lens degree(°)θ1/2	Input voltage(V)	Typical operating current(mA)	Typical consumption(W)	Typical luminance(lm)	IK rate
B4TA1257	12×2W	B32	25°	24V DC	1200	28.8	Cool white=2067 Warm white=1610	09

