



Architectural and Landscape Spot Light

LED Colour Temperature


2000K
3000K
6000K

Optics




FB06	
F06B3F09	9°
F06B3D15	15°
F06B3D20	20°
F06B3D30	30°
F06B3D45	45°

FB06



Outer Dimensions



Unit:mm

Material Specifications

Housing	12° Die-casting dark grey powder coated aluminum. T=60-80um Adhesion of ISO class 1/ASTM class 48
lens	All-in-one optical lens efficiency>85%
Light Window	Tempered glass T=4mm
Cable gland	IP68 PG-9 PA66
Gasket	Tooling shaped seal
Bracket	Powder coated aluminum
Power Cable	H05RN-F 2X1.0mm ² L=2.0m(low voltage) H05RN-F 3X1.0mm ² L=2.0m(high voltage)
Dimmable Support	Triac PWM 1-10V Dali



Housing color Option

Basic	Secondary	
Sanded Dark Grey KAP 7037	Silver Grey KAP 9022	Sanded Black RAL9005

Item	Light source	Lens	The manufacturer selected lens degree(°)θ1/2	Input voltage(V)	Typical operating current(mA)	Typical consumption(W)	Typical luminance(lm)	IK rate
FB3BH0657	6×2W Single color	FB06	20°	24VDC 120/240	24V = 558 120V = 97 240V = 57	24V = 13.4 120V = 11.5 240V = 12.6	Cool white=1117 Warm white=835	08

