

COB

Landscape Flood Light



LED Colour Temperature

3000K
6000K

Optics



B55

L01125050LK 18°
L01245050LK 28°
L01385050LK 38°

B55



18°




28°



38°

Outer Dimensions

Unit:mm



Material Specifications

Housing	12" Die-casting dark grey powder coated aluminum, T=60-80µm. Adhesion of ISO class 1/ASTM class 4B
Front cover	Hard chrome-plated Stainless steel (SUS 304*, 316* optional)
Light Window	Tempered glass, T=4mm
Gasket	Tooling shaped seal
LED	COB LED 6W
Cable gland	IP-68 PG-9 PA66
Bracket	Powder coated aluminum
Reflector	Optical Reflector efficiency 90%
Power Cable	H05RN-F 2X1.0mm² L=2.0m (low voltage) H05RN-F 3X1.0mm² L=2.0m (high voltage)
Mounting base	12" Die-casting dark grey powder coated aluminum

Housing Color Option

Basic	Secondary
Sanded Dark Grey KAP 7037	Silver Grey KAP 9022
	Sanded Black RAL 9005

Item	Light source	Lens	The manufacturer selected lens degree(°)1/2	Input voltage(V)	Typical operating current(mA)	Typical consumption(W)	Typical luminance(lm)	IK rate
B3FTM0126	1x6W	B55	28°	24VDC 120/240	24V = 270 120V = 65 240V = 37	24V = 6.5 120V = 7.7 240V = 7.8	Cool white =490 Warm white =444	04

