


JRF3-3



Product Dimension



- Original design, cover made of high-strength tempered glass, anti-impact, abrasion resistant.
- Powerful features, easy to control, can achieve the logarithmic dimming and mixed light in the distance of less than 1 m, transform the light soft and brilliant.



可调角度设计
Adjustable Angle



呼吸器
Respirator



地插
Ground spike



遮光罩
Visor

Product Specification

Product Code	JRF3-3	JRF3-3/3×2.2W
LED Quantity	3pcs	3pcs
Rated Power	4/3.5W	9/8.5W
Color	Single /RGB	Single /RGB
Luminous Flux	327/140 lm	517/221 lm
Installation Pipe Diameter	Φ8.5×15mm	Φ8.5×15mm
Input Voltage	AC100-277V	AC100-277V
Frequency Range	50/60Hz	50/60Hz
Control Mode	CC/DMX512	CC/DMX512
Beam Angle	10° 25° 40° 60°	10° 25° 40° 60°
Temperature of Working Condition	-35-50°C	-35-50°C
Humidity of Working Condition	10-90%	10-90%
LED Lifetime	70000h	70000h
Protection Grade	IP66	IP66
Net Weight	0.92kg 16.5kg	0.92kg 16.5kg
Gross Weight	1.05kg 18.9kg	1.05kg 18.9kg
Packing Size	140x160x220mm 530x530x65mm	140x160x220mm 530x530x65mm

Packing size is outer size of box
All parameters are measured at 25°C ambient temperature, 35% humidity experimental environment
Luminous flux is the maximum value among all kinds of light distribution.

