

Linear Beam 120/240V
IP-66 Ultra Slim Light Bar



S6JC1235
S6JC2435

LED COLOUR TEMPERATURE

2000K · 3000K · 6000K

OPTICS



B15

S6JC1235



10°
33°


S6JC2435




10°
33°

OUTER DIMENSIONS

Unit:mm




S6KC1235



S6JC2435



High voltage input (100V-240V) power cord wiring model



MATERIAL SPECIFICATIONS

Housing	Extruded aluminum anodized finishing or powder painting
Lens	Optical lens efficiency≥85%
Light window	Tempered glass,T=3mm
Gasket	Glass and housing are silicone sealed
LED	Single color ORSAM LED
Operating temperature	-20°C~40°C
Bracket	Hard chromeplated stainless steel SUS 304#
Power Cable	H03VV-F 3X0.1mm² L=0.5m(high voltage)

Optional Honeycomb Louver



TECHNICAL DATA

Item	Light source	Lens	The manufacturer selected lens degree(°)θ1/2	Length L=(mm)	Input voltage(V)	Typical operating current(mA)	Typical consumption(W)	Typical luminance(lm)	IK rate
S6JC1235	12×1W	B15	10° 33°	500	120/240V	120V = 130 240V = 65	120V = 15.0 240V = 15.0	Cool white=1080 Warm white= 864	02
S6JC2435	24×1W	B15	10° 33°	1000	120/240V	120V = 295 240V = 163	120V = 35 240V = 35	Cool white=2140 Warm white=1976	02