

Linear Beam 120/240V
IP-66 Slim Light Bar



S6KC1257
S6KC2457

LED COLOUR TEMPERATURE

2000K · 3000K · 6000K

OPTICS



B27
L01 1/8" D021YM

B27




10°
30°
S6KA1257




10°
30°
S6KA2457

OUTER DIMENSIONS

Unit:mm



S6KC1257



S6KC2457



High voltage input (100V-240V) power cord wiring model



HSO type
Single cable, open wire ends type




HSP type
Single cable + male plug type

MATERIAL SPECIFICATIONS

Housing	Extruded aluminum anodized finishing or powder painting
Lens	Optical lens efficiency ≥ 85%
Light window	Tempered glass, T=4mm
Cable gland	IP68 PG-9 PA66
Gasket	Glass and housing are silicone sealed
LED	Single color ORSAM LED
Operating temperature	-20°C ~ 40°C
Bracket	Hard chrome plated stainless steel SUS 304#
Power Cable	H05RN-F 2X1.0mm² L=0.5m (low voltage)

Optional Honeycomb Louver



TECHNICAL DATA

Item	Light source	Lens	The manufacturer selected lens degree(°) θ1/2	Input voltage(V)	Typical operating current(mA)	Typical consumption(W)	Typical luminance(lm)	IK rate
S6KC1257	12×1.5W	B27	10° 30°	120/240V	120V = 203 240V = 105	120V = 24.4 240V = 24	Cool white = 2358 Warm white = 1838	05
S6KC2457	24×1.5W	B27	10° 30°	120/240V	120V = 414 240V = 212	120V = 48.0 240V = 48.3	Cool white = 4912 Warm white = 3742	05