

# Recessed LED Soft Beam Stair Light & Wall Light



## LED COLOUR TEMPERATURE



2000K · 3000K · 6000K

## OPTICS

N/A

## OUTER DIMENSIONS & ACCESSORIES

Unit:mm



Mounting Sleeve 071 #

## MATERIAL SPECIFICATIONS

- HOUSING** | 12# Die-casting grey powder coated aluminum  
T=60-80µm Adhesion of ISO class 1/ASTM class 4B
- BEAM WINDOWS** | 50% transmittance PC cover
- WATERPROOF SEAL** | Rubber seal
- OPERATING TEMPERATURE** | -20°C~40°C
- POWER CABLE** | H05RN-F 2X1.0mm<sup>2</sup> L=0.5m(low voltage)  
H05RN-F 3X1.0mm<sup>2</sup> L=0.5m(high voltage)
- MOUNTING SLEEVE** | ABS 071#
- DIMMABLE SUPPORT** | Triac PWM 1-10V Dali

## FRONT COVER COLOR



## MOUNTING SLEEVE CHARACTERISTIC



## TECHNICAL DATA

ITEM	LIGHT SOURCE	INPUT VOLTAGE(V)	OPERATING CURRENT(MA)	CONSUMPTION(W)	LUMINANCE(LM)	IK
D1BO0136	1×2W	24V DC 120/240	24V = 110 120V = 46 240V = 26	24V = 2.6 120V = 2.8 240V = 3	Cool White = 19 Warm White = 20	09

## PHOTOMETRIC CURVES

