

Wall Mounting Landscape Light




Double Side

LED COLOUR TEMPERATURE

2000K · 3000K · 6000K

OUTER DIMENSIONS & ACCESSORIES

Unit:mm



OPTICS

N/A

MATERIAL SPECIFICATIONS

- HOUSING** | 12# Die-casting dark grey powder coated aluminum
| T=60-80µm. Adhesion of ISO class 1/ASTM class 4B
- LIGHT WINDOW** | PC T=6mm
- GASKET** | Tooling shaped seal
- DRIVER** | Main voltage 100V-240V driver inside builded
- OPERATING TEMPERATURE** | -20°C~40°C
- POWER CABLE** | H05RN-F 2×1.0mm² L=0.3m(low voltage)
| H05RN-F 3×1.0mm² L=0.3m(high voltage)

HOUSING COLOR OPTION



Dark Grey
RAL 7037



Sanded White
RAL 9003



Sanded Black
RAL9005

TECHNICAL DATA

ITEM	LIGHT SOURCE	INPUT VOLTAGE(V)	OPERATING CURRENT(MA)	CONSUMPTION(W)	IK
D7AC0237	2×3W NICHIA	24V DC 120/240	24V = 268 120V = 138 240V = 73	24V = 6.2 120V = 8.5 240V = 8.6	06

PHOTOMETRIC CURVES

