

## Wall Mounting Ceiling Down Light



### LED COLOUR TEMPERATURE


3000K · 6000K

### OPTICS



### OUTER DIMENSIONS & ACCESSORIES

Unit:mm



### MATERIAL SPECIFICATIONS

- HOUSING MATERIAL** | Extruded aluminum alloy #6063
- PAINTING** | Powder coating ,T= 60-80 um./Adhesion of ISO class 1/ASTM class 4B
- REFLECTOR** | Optical reflector, efficiency≥85%
- LIGHT SOURCE** | NICHIA
- POWER CABLE** | H05RN-F 2X1.0mm<sup>2</sup> L=0.3m(low voltage)  
| H05RN-F 3X1.0mm<sup>2</sup> L=0.3m(High voltage)
- OPERATING TEMPERATURE** | -20°C~40°C

### HOUSING COLOR OPTION



Beam Effect Demo

### TECHNICAL DATA

ITEM	LIGHT SOURCE	LENS	LENS DEGREE(°)Ø1/2	INPUT VOLTAGE(V)	OPERATING CURRENT(MA)	CONSUMPTION(W)	LUMINANCE(LM)	IK
<b>R8CI0170</b>	1×18W	R20	30°	24V DC 120/240	24V = 840 120V = 172 240V = 91	24V = 20.4 120V = 20.6 240V = 20.9	Cool White = 2400 Warm White = 2105	06

### PHOTOMETRIC CURVES

